

AUTEL®

MaxiCharger AC Lite – 7.4kW



Technical Specifications

Product Information

| | |
|---------------------------------------|---|
| Charging mode | Type 2 |
| Input/output power rating and current | Single phase up to 7.4kW/32A |
| Input/output voltage | 230V±15%, single phase; 50Hz |
| Network type | TT, TN |
| Connector type | IEC 62196 type 2 plug, 5m |
| Internal RCD | AC 30mA, DC 6mA |
| Protection | Overcurrent, overvoltage, undervoltage, integrated surge protection |
| Power measurement accuracy | ±2% accuracy class |

General Characteristics

| | |
|-----------------------------|--------------------------------|
| IP and IK rating | IP65, IK08 |
| Operating altitude | 2000m |
| Operating temperature range | -30°C~+50°C |
| Storage temperature range | -40°C~+70°C |
| Mounting | Wall or floor using a pedestal |
| Dimensions (H×W×D) | 336 x 187 x 97 mm |

User Interface

| | |
|-------------------------|--------------------------------------|
| Status indication | LED/APP |
| User interface | Autel Charge APP; Autel Charge Cloud |
| Connectivity | Bluetooth, Wi-Fi |
| Communication protocols | OCPP 1.6J (Autel cloud only) |
| User authentication | APP, RFID card, Autostart |

Software Update

OTA updates via web portal

Certification and Standards

| | |
|----------------------------------|---|
| Safety and compliance | IEC 61851-1, IEC 62311, IEC 62479, IEC 62955, IEC 61439-1/ -7 |
| CertificationCodes and standards | CE (TUV) |
| Warranty | 2 years |
| Fire class | UL94 V0 |
| Overvoltage category | III |
| OCPP Compability Test | OCA |
| Product Design Life | More than 10 years |

* All pictures shown are for illustration purpose only. Actual product and specifications may vary due to product enhancement

AUTEL®

Wilbest

info@wilbest.co.nz

021 173 1730